




Cross-Domain Data Transfer



Hardware Data Diode protecting your most confidential Domains while transferring data

What is OWA-3U-10/25G

OWA-3U-10/25G **GOV & Defense Edition** is a high-assurance, hardware-enforced Cross-Domain Gateway designed for extreme performance and reliability, enabling controlled data and file exchange between environments of different security levels at sustained rates from 1+ Gbps. It enforces strict physical unidirectionality, while also supporting bidirectional asynchronous file and data transfer. It thus ensures full operational capabilities combined with air-gap-grade isolation security that software-based guards and firewalls cannot match.

Its secure-by-design architecture enables high-confidence data release through deep file inspection, advanced file filtering policies, and dual anti-malware controls operating at fiber speed, without introducing packet loss or data corruption. Built for the most demanding governmental and defense environments, and integrating an optional ANSSI-qualified or up-to-EAL7+ certified Data Diode, Cyberium's OWA product line provides a trusted foundation for Cross-Domain Data Exchange while preserving confidentiality, integrity, availability, and accreditation constraints.

OWA-3U-10/25G



DATASHEET GOV & DEFENSE EDITION

KEY CHARACTERISTICS

- True Bandwidth**
10+ Gbps / 25+ ⁽¹⁾ Gbps sustained on a single link, optimized for encrypted files transfer
- Compliance up to EAL7+**
Choose between various optical Data Diode options, providing the desire certification level up to **Common Criteria EAL7+** ⁽¹⁾
- Strict Unidirectionality, Both Ways**
No returning data link, not even on a separate channel for flow control. Supports bidirectional asynchronous data flows in total security ⁽²⁾
- Complete Physical Separation**
Upstream and downstream proxies remain 100% physically separated
- Deep Malware deletion**
2-layer real-time virus inspection detects and deletes 95% of malware at fiber speed
- Advanced Filtering & Signature**
Multiple per-file or per-file-type, XML-based content filtering and Digital Signature. Eased support for tailored filtering mechanisms
- Absolute Reliability**
 - 0-packet loss[Ⓟ], 0-file loss[Ⓟ], and 0-file corruption[Ⓟ]
 - Automatic traffic recovery
 - Above-grade MTBF
- IT Protocols Compatibility**
A vast range of protocols and file systems supported. See a full list at the back
- Seamless Deployment**
Transparent to end-users. No change in the network. Easy admin. No extra workload for administrators.

(1) Subject to eligibility - please get in touch with us

(2) Requires a 2nd OWA product for the return link

Technical Specs

HARDWARE APPLIANCE

Ordering SKU	OWA-3U-10G or OWA-3U-25G
Mounting Rack	19" Rack Mounting, Rack kit included, Sliding rails. 2U Rack Space for the two proxies + 1U (optional) for the Optical Data Diode
Dimensions & Weight <small>Per proxy server, without Data Diode</small>	H 42.8 mm W 482 mm D 816.92 mm 17.53 Kg / 38,64 Lb
Operating T°	5 °C to 45 °C (41 °F to 113 °F) with no direct sunlight on the equipment
Standards	Enterprise-Class Mission-Critical Hardware MTBF > 50 000 hr
Electrical/ Power <small>Per proxy server</small>	100-240 V AC - Avg consumption: 250 W 2x 800 W PSU

NETWORK & CONNECTIVITY

Port / Interfaces <small>Per proxy server</small>	4x 1/10 Gbps (SFP+), 2x 25 Gbps (SFP+)
USB / Other <small>Per proxy server</small>	2x USB-port, 1x VGA-port
Max end-to-end Throughput	10 field upgradable to 25 Gbps - True deliverable capacity
File Sending Benchmark	Above 1000 files of 1 MB sent /sec at 10 Gbps. Max file size 500 GB, upgradable.
PROTOCOLS	
IT Protocols	MQTT, UDP, HTTP/S API, SMTP
File Transfer	SFTP, FTP/S/ES No degradation of bandwidth with encryption.
Data Transfer	MS SQL / Oracle Database Replication (Incremental Backups) SQL Real Time Data Replication (Changes)

SECURITY COMPONENTS

Supported scenarios	<ol style="list-style-type: none"> Public/Lower trust network to Protected or Confidential network (with A/V and filtering) Protected/Confidential network to Public or Lower trust network (with optional filtering) Asynchronous bi-directional (half-duplex) combinaison of scenarios 1. and 2. (2x OWA)
Included Optical Diode - 1U option	Thalès Elips (passive - ANSSI FR / eq. EAL 7+) ⁽¹⁾ Sentyron 10 G (active - EAL 7+) ⁽¹⁾ Allentis Tapics (passive - ANSSI FR)
Antivirus	Dual A/V Scanning with Deep File Inspection Powered by BitDefender® and ClamAV® engines
File filtering	Based on true file type detection and JSON/XML content inspection
OS	Hardened OS based on AlmaLinux SE


MANAGEABILITY & RESILIENCE

High Availability	Active/Active - automated fail-over with the purchase of a second OWA appliance + High Availability Option
Traffic Buffering	Up to 1-week ⁽²⁾ automatic replay of past traffic in case of downstream network unavailability.
Solution Monitoring	Either through Syslog OR Web GUI central console enables monitoring of traffic, health and performances, downstream of the proxy appliances
Logging	Every configuration change and every traffic is logged
Administration Account	Separated on the upstream and downstream proxies
Config. saving / restore	Locally, on USB or on the network

How does it work

OWA / AGENTS combined architecture:

OWA-3U-10G/25G is entirely compatible with Cyberium AGENTS, an exclusive Suite of Software Replicator Agents
 - See Cyberium OWA AGENTS Datasheet for more details



Gov Portfolio Overview

See also

OWA-3U-1G

1 Gbps

> Current Datasheet

✓ OWA-3U-10G

10 Gbps

✓ OWA-3U-25G

25 Gbps

The OWA **Gov & Defense Edition** product line relies on two primary hardware platforms: one engineered for 1 Gbps environments, and a extremely high-performance platform supporting 10 Gbps up to 25 Gbps data transfers. This architecture enables a scalable response to a broad spectrum of operational requirements, from standard data exchange to highly demanding use cases involving large data volumes at real-time. Both platforms deliver sustained throughput, low and deterministic latency, and the same hardware-enforced security guarantees, allowing performance to scale without compromising security or reliability.

(1) Option subject to prior regulatory approval.

(2) Buffer capacities are calculated based on an average traffic load at 10 Gbps bandwidth.

Member of:



HEXATRUST
CLOUD CONFIDENCE & CYBERSECURITY

cyberium.solutions
contact@cyberium.solutions